

## Technical Information Sheet Article No. 1368

# AGE

Alkali-free stripping agent, removes graffiti and paints pore deep.  
Biodegradable

### Range of use

Remmers AGE removes dispersion, pure acrylate and synthetic resin varnishes, cellulose nitrate lacquer, spirit varnishes, matting agents, polishes as well as graffiti from all wood surfaces, metals and mineral substrates.

### Property profile

Remmers AGE is a water emulsifiable cleaning product in paste form. It has a long action time which allows deeper lying paint remains and layers of varnish to be reliably removed.

- Alkali-free
- No chlorinated hydrocarbons
- Biodegradable according to DIN EN 29888, Test Report LGA Bayern AZ 9544039
- Listed in the BAST list of tested anti-graffiti systems, UBA number 07530119 (German Federal Environment Office).

### Directions

Apply the material generously but evenly with a brush or roller (no plastic bristles) or airless equipment. The stripper is removed with a filling knife or a high pressure cleaner with a water temperature of 70 - 90 °C. Cover plastic sur-

### Characteristic data of the product

#### Characteristic data of the product in the packaged state:

Density:	1.05 kg/l
pH value (20 °C):	approx. 8.5 at 10 g/l water

faces. The stripping effect depends on the substrate and the material to be stripped. Work should always be carried out wet-on-wet. At 20 °C, the action time can range from 1 to 4 hours and correspondingly longer at lower temperatures. The reaction time can be increased by covering with a thin plastic sheet.

### Notes

A sufficiently large trial area should always be set up to test compatibility with the substrate, its suitability and to determine application rates. When working indoors, make sure there is good ventilation and observe job safety rules. Observe legal provisions for leading into the sewage system and/or disposing of the product mixed with the removed paint.

### Packaging, application rate, shelf-life

#### Packaging:

0.75 l 5 l and 25 l tin containers

#### Application rate:

Depending on the layer thickness of the old coating, approx. 300 - 500 g/m<sup>2</sup>

#### Shelf-life:

At least 12 months in closed containers stored cool but frost-free.

### Safety, ecology, disposal

Further information on safety when transporting, storing and handling as well as disposal and ecology is found in the latest Safety Data Sheet.

**Personal protective equipment is required for spraying procedures. Use respiratory protection with a combination filter at least A/P2 (made by e.g. Dräger). For suitable protective gloves, see Safety Data Sheet. Wear closed work clothes.**

The statements above are compiled from our field of production and according to the latest technological developments and application techniques.

Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet. Any statements made beyond the contents of this information must be confirmed in writing by the producer.

In all cases, our general conditions of sale are valid. With the publication of this Technical Information Sheet all previous editions are no longer valid.

GB 1368 - 10.07



Remmers (UK) Limited Crawley  
United Kingdom  
Tel: +44(0) 845 373 0103  
Fax: +44(0)845 373 0104  
[www.remmers.co.uk](http://www.remmers.co.uk)

Remmers (Far East) Pte. Ltd.  
Singapore  
Tel: +65 6 7410277  
Fax: +65 6 7417158